



FR601 FAMILY OF SDI BOARDS



The FR601 family includes a variety of innovative and cost effective SDI products, all designed as single, plug-in boards. Up to three of these boards may be housed in the FR601, 1RU frame and power supply (optional redundant p.s. available).

CARDKEY 2: Linear keyer with adjustable transparency, card edge control plus GPI, or optional remote panel.

MASTERKEY CK-2: Chroma keyer with adjustable hue and key level, for blue and green screen backgrounds.

DFB200: Frame accurate fade to black with GPI.

VBI-232D: Encoder/decoder for transmission of remote control data in the Vertical Ancillary Space.

DCB-21: Closed Captioning positioner/bridge prevents previously encoded captions from blocking local road/weather warnings and EAS crawls. Also bridges CC data around 'unfriendly' processing equipment.

CCA-21: Closed Captioning alarm, constantly monitors SDI program video to ensure valid closed captioning.

DSC300: Signal comparator and alarm, to compare two SDI streams and trigger GPO's on any difference or impairment of video or embedded audio.

DMA200: Frame accurate A/B mix amp with GPI.

CC-101D: Closed Captioning encoder encodes CC data on line 21 of an SDI signal.

VC-1D: V-Chip rating encoder generates & inserts program rating data onto line 21 of an SDI signal.

broadcast video systems corp.

10 Woltner Way, Markham, Ontario L3R 4R4

Ph(905)305-0565 Fax(416)946-1964 E-mail: bvs@bvs.ca Website: www.bvs.ca